

Thrust Ball Bearing

DATA TABLE - DOUBLE ACTING



Part number	Principal dimensions			Basic load ratings			Speed limits		Weight	Radius		Dimensions	
	d	D	H	Dynamic	Static	Fatigue	Grease	Oil		rs min	r1s min	D1	B
				Cr	Cor	Pu		rpm					
	mm			kN			1 min ⁻¹		Kg	mm			
52217	70	125	55	92	251	11,41	1600	2200	2,34	1,0	1,0	88	12
52317	70	150	87	206	489	21,19	1100	1600	6,43	1,5	1,0	88	19
52218	75	135	62	117	326	14,46	1500	2000	3,22	1,1	1,0	93	14
52318	75	155	88	213	524	22,21	1000	1500	6,60	1,5	1,0	93	19
52420	80	210	150	368	983	37,11	700	950	26,60	2,0	1,0	103	33
52220	85	150	67	147	410	17,19	1300	1800	4,29	1,1	1,0	103	15
52320	85	170	97	236	596	23,99	950	1400	8,90	1,5	1,0	103	21
52322	95	90	110	280	754	34,27	850	1200	13,80	2,0	1,0	113	24
52222	95	160	67	148	431	17,35	1200	1700	4,68	1,1	1,0	113	15
52224	100	170	68	154	472	18,47	1100	1600	5,24	1,1	1,1	123	15
52324	100	210	123	325	931	33,99	800	1100	17,20	2,1	1,1	123	27
52226	110	190	80	203	622	23,08	950	1400	7,74	1,5	1,1	133	18
52228 M	120	200	81	215	669	24,04	950	1400	8,95	1,5	1,1	143	18
52230 M	130	215	89	244	768	26,58	900	1300	10,60	1,5	1,1	153	20
52330 M	130	250	140	377	1200	39,57	670	900	27,10	2,1	1,1	154	31
52232 M	140	225	90	247	803	27,02	850	1200	12,20	1,5	1,1	163	20
52332 M	140	250	140	470	1570	51,10	630	850	26,20	2,1	1,1	154	31
52234 M	150	240	97	269	874	28,45	800	1100	15,20	1,5	1,1	173	21